J.C GROUP™

Rima Machines Pvt Ltd

No big words but a promise to work





JC - 6 ECO TFO Twister (Spun)

Technical specifications

			JC-6-DD-90-110	JC-6-DD-110-110	JC-6-DD-110/130
No. of Spindles		:	240-24-432	240-24-432	240-24-432
Spindle Dia		:	90 mm	110 mm	110 mm
Pot Dia		:	110 mm	110 mm	130 mm
Count Range	Ne	:	30/2 - 50/2	20/2 - 140/2	20/2 - 50/2
Twist Range	TPI	:	4 - 50	4 - 50	4 - 50
Spindle Pitch	mm	:	208	208	208
Spindle Speed (Mechanical)	RPM	:	12000	12000	12000
Tension Device		:	Capsule Type	Capsule Type	Capsule Type
Spindle Drive		:	Tangential Belt	Tangential Belt	Tangential Belt
Max. Yarn Speed		:	55 mts./min.	55 mts./min.	55 mts./min.
Starting System*		:	Slow Start by Star - Delta	Slow Start by Star - Delta	Slow Start by Star - Delta
Parameter Display		:	Provided	Provided	Provided
Connected Load	KW	:	2 x (3.75 - 7.5)	2 x (5.5 - 11.2)	2 x (5.5 - 11.2)
Feed Package					
Tube Size		:	32 x 37 x 170	37 x 42 x 170	37 x 42 x 170
Max. Dia with Yarn		:	104 mm	104 mm	127 mm
Yarn Content		:	450 - 550 gms	450 - 550 gms	750 - 850 gms
Take-up Package					
Concity		:	0 - 5*57'	0 - 5*57'	0 - 5*57'
Traverse		:	152 mm	152 mm	152 mm
Max Dia with Yarn		:	200 mm	200 mm	200 mm
Yarn Content		:	2.0 Kgs	2.0 Kgs	2.0 Kgs

M/c. Dimensions

No. of Spindles	:	240	264	288	312	336	360	384	408	432
M/c. Length mm	:	15300	16624	17948	19272	20596	21920	23244	24568	25892
M/c. Width mm	:	---------- 720 ----------								
M/c. Height mm	:	---------- 1995 ----------								

Product Range :

- TFO Twister for Cotton, Spun & Blended Yarn having pot dia 110 / 120 / 130 / 140 / 150 / 170 mm
- TFO Twister for Cotton, Spun and Filament Industrial Yarn having pot dia 180 / 200 / 260 /300 mm
- Cable Corder for making Tyre Cord, Industrial or Carpet Threads
- Elastic / Latex / Spandex Yarn Single as well as Double Covering Machines
- Elastic Yarn Warping Machine
- Lycra Warping for Warp Knitting
- Rubber Thread Spool Winder
- Yarn Warping for Narrow Fabric
- Hank to Bobbin winder for Real Silk
- Primary / Secondary TFOs for making Embroidery, Sewing, Fishnet and Industrial Threads
- High Bulk Yarn Machine
- High Take-up, Low Twist TFO having Delivery Speed up to 250 MPM
- 70 / 80 / 90 / 110 / 120 / 130 / 150 mm Pot TFO Twister for Filament, Pure Silk and Viscose Yarn
- 'S' & 'Z' Covering Machine
- Various Types of Cop Winders
- 2 / 3 / 4 ply Assembly Winder for Spun Yarn having Individual Motor / Drum
- 2 / 3 / 4 ply Assembly Winder for Real Silk
- Hank to Bobbin winder for Real Silk
- 4 to 24 ply Assembly Winder with External Creel having Individual Motor/Drum

THE INFORMATION SUPPLIED IN THE BROCHURE IS FOR GUIDANCE ONLY.
WE RESERVE OUR RIGHT TO MODIFY THESE AT ANY TIME.

J C GROUP™

Rima Machines Pvt Ltd

Plot No.C-23/3-5, Road No.15, Hojiwala Ind. Estate, Vanz, SACHIN SURAT - GJ 394230 INDIA
Call: +91 93747 38545 / 98251 83836 Web: www.jcmachine.com Email : rimamachines@gmail.com / info@jcmachine.com

Pixel Image 098251 86810